# Full Body Harness

LOOK AT:

|--|

### OHSA 1926.502(d)(21)

Personal fall arrest systems SHALL be inspected prior to each use for wear, damage, and other deterioration, and defective components SHALL be removed from service.



#### 6.1 Inspection

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year.

## Frequency of inspection in the following categories:

General Industry: \_\_\_\_\_ Construction: \_\_\_\_\_

Your Organization: \_\_\_\_\_\_ Manufacturer: \_\_\_\_\_

# Manufacturer of equipment:

Name of Manufacturer: \_\_\_\_\_

Serial #:	 Model #:	

Date of Manufacture: \_\_\_\_/\_\_\_/

#### Inspection:

Date: \_\_\_\_/\_\_\_\_/

Name of competent person:

# Name of user (authorized person):



	<b>3</b> STITCHING <b>4</b> LABELS/TAGS		
1	HARDWARE	$\checkmark$	$\mathbf{X}$
Rust/c	orrosion		
Deforn	ned/bent		
Burrs/	cracks		
Weld s	pots/slag		
Missin	g rivets		
Spring	5		
Functio	onality		
Other			

1 HARDWARE

2 WEBBING

2	WEBBING	$\checkmark$	X
Cuts/b	urns/holes		
Excess	ive wear		
Excessive UV damage			
Chemical attack			
Other			

3	STITCHING	$\checkmark$	X
Missin	g		
Loose			
Broker	1		
Other			

4	LABELS/TAGS	$\checkmark$	X
Missing	g		
Illegibl	e		
Dates			
Other			



PASS X FAIL